

Burglar Resistant Fixed Glazing

Burglar Resistance**RC 4****tested acc. to EN 1627**

Optional Audited Additional Functions

- Fire Protection	EI ₂₃₀ / F30 bis EI ₂₉₀ / F90	tested acc. to EN 1363-1
- Impact Resistance	P1A bis P5A	tested acc. to EN 356
- Penetration Resistance	P6B bis P8B	tested acc. to EN 1063
- Bullet Resistance	FB4-NS to FB7-NS	tested acc. to EN 1522
	BR1-NS to BR7-NS	tested acc. to EN 1063
- Explosion Resistance	up to 20 kPa	tested acc. to EN 13124-1
- Blast Resistance	ER1-NS bis ER4-NS	tested acc. to EN 1522

Range of Dimension

Width from 500 mm to 2000 mm
Height from 500 mm to 2000 mm

Technical Specification and Tender Text

Product:	FVG SEC / RC 4 burglar resistant fixed glazing brand Buchele tested acc. to EN 1627
Window Type:	FVG SEC / RC 4
Resistance Class:	RC 4
Structural Opening: x mm
Frame and Glazing:	4-sided circumferential block frame in which a P6B safety glazing is inserted, which is fixed with a 4-sided circumferential glass holding frame.
Surface:	galvanized and primed with 2K-PUR primer (Very High Solid) similar RAL 7035.

Supplementary Equipment

BUCHELE DELUXE:	The exclusive surface coating.
------------------------	--------------------------------

