

## Bullet Resistant Fixed Glazing

**Bullet Resistance**                      **FB 6 NS**                      **tested acc. to EN 1522**

### Optional Audited Additional Functions

- Fire Protection	EI <sub>230</sub> / F30 bis EI <sub>290</sub> / F90	tested acc. to EN 1363-1
- Burglar Resistance	RC2 / RC3 / RC4	tested acc. to EN 1627
- Impact Resistance	P1A bis P5A	tested acc. to EN 356
- Penetration Resistance	P6B bis P8B	tested acc. to EN 1063
- Explosion Resistance	up to 20 kPa	tested acc. to EN 13124-1
- Blast Resistance	ER1-NS bis ER4-NS	tested acc. to EN 1522

### Range of Dimension

**Width**    from 500 mm to 2000 mm  
**Height**   from 500 mm to 2000 mm

## Technical Specification and Tender Text

<b>Product:</b>	<b>FVG SEC / FB 6 bullet resistant fixed glazing brand Buchele tested acc. to EN 1522</b>
<b>Window Type:</b>	<b>FVG SEC / FB 6</b>
<b>Resistance Class:</b>	<b>FB 6 NS</b>
<b>Structural Opening:</b>	<b>.... x .... mm</b>
<b>Frame and Glazing:</b>	4-sided circumferential block frame in which a FB 6 safety glazing is inserted, which is fixed with a 4-sided circumferential glass holding frame.
<b>Surface:</b>	galvanized and primed with 2K-PUR primer (Very High Solid) similar RAL 7035.

## Supplementary Equipment

**BUCHELE DELUXE:**                      The exclusive surface coating.

